



- HANDICAPPED TOILET NOTES**
1. WATER CLOSET SEAT 18"20" OF
  2. GRAB BAR 1 1/2" DIA. 1 1/2" CIR. OF WALL & 32 1/2-33 1/2 A.F.F. 24" MIN. LENGTH CENTERED ON LEADING EDGE OF W.C.
  3. MIRROR 40" A.F.F. SHELF 40" MAX.
  4. LAVATORY HT. MAX. 34" BOTTOM CIR. MIN. 28" AFF

CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND SITE CONDITIONS BEFORE PROCEEDING WITH WORK

DATE: 11-10  
 REVISIONS: CHANGE NOTES  
 DRAWN BY: MANUEL SOTO  
 COMM. NO.: 1-546  
 DATE:

MEDICAL FOR BUILDING  
 DR. MANUEL SOTO  
 BELLE GLADE, FL.

DEKONSCHIN & ASSOCIATES INC.  
 architect / planner

NAPLES (813) 774-5313

SHEET NO. A-3  
 OF 15  
 11-17

- FIRE EXTINGUISHER NOTES:**
1. EXTINGUISHERS SHALL BE INSTALLED IN ACCORDANCE WITH THE NATIONAL FIRE PROTECTION STANDARD "PORTABLE FIRE EXTINGUISHERS" NFPA - 10
  2. MOUNTING HARDWARE (SCREWS, RIVETS, ETC.) SHALL BE OF THE PROPER TYPE AND SIZE TO ASSURE A POSITIVE MOUNTING.
  3. THE EXTINGUISHER SHALL BE MOUNTED IN ORDER THAT THE TOP IS NOT MORE THAN 3 1/2 FEET TO 5 FEET ABOVE FINISHED FLOOR. IF DETAILS IS INCLUDED IN THE PLANS, REFER TO DETAILS.
  4. FE-1 10 LB. CAPACITY, MULTI PURPOSE (ABC) DRY CHEMICAL AMMONIUM PHOSPHATE FIRE EXTINGUISHER AS MANUFACTURED BY "W. D. ALLEN" WITH HIGH IMPACT FLAME RETARDANT A.D.S. CABINET 105-10 AS MANUFACTURED BY "CATO PLASTICS INC."

FLOOR PLAN W/ NOTES

SCALE 1/4" = 1'-0"