

MERIDIAN FLEX SUITES
INDUSTRIAL CONSTRUCTION CRITERIA
16221 Lee RD Fort Myers FL 33912
August 14, 2024

Hurricane Protection:

Building Rated to 155 MPH wind load.

All windows and doors are impact rated.

Roof:

Roof to be an A Frame roof

Floors:

All floors to be a minimum 5", 3000 PSI smooth trowel finish concrete slab over vapor barrier on graded and compacted fill.

Walls:

Demising walls: 6" metal studs, insulated, with 5/8" fire-rated gypsum board to roof deck, primed.

Exterior walls: Masonry block to receive furring strips and 5/8" fire-rated gypsum board to ceiling line, primed.

Firewall to be 6" metal studs

Doors:

Front door: One (1) 3'0" x 7'0" storefront. Building standard hardware including lockset, deadbolt with door closer, weather stripping and threshold. .

Garage Door: Paneled garage door (14'W x 14'H) with windows

Windows:

All windows to be Low E Impact glass, ¼ gray tint.

Fire Protection:

Fire Sprinkler

Developer will install a complete automatic fire sprinkler system (wet), as required by code. Any modifications to base design required by Owner's interior design or proposed use or occupancy shall be performed by the Developer's fire protection contractor for said site and shall be at Owner's sole cost and expense.

Fire Alarm

Developer will provide a fire alarm system as required by the local jurisdiction having authority. Any modifications or additional fire systems and alarms required by Owner's interior design or proposed use, or occupancy shall be performed by the Developer's contractor for said site and shall be at Owner's sole cost and expense.

HVAC - (Heating, Ventilation, and Air-Conditioning):

1. 3-ton split system AC with fiberglass duct board trunk lines from front to back of unit.
2. Provide a standard heat/cool thermostat mounted 5'-0" AFF in retail space.
3. One (1) exhaust fan in the restroom.
4. The system shall be designed to meet applicable energy codes and standard mechanical code or SFBC as applicable.

Electrical Supply:

Panels

225 AMP

Outlets

Buyer _____

Seller _____

1. Recessed duplex outlets @ 12'-0" on center (OC) along demising walls.

Light Switches

1. One (1) light switch in restroom (combination light switch/exhaust fan control) with occupancy sensor.
2. One (1) switch is provided at the entrance.

Bathroom

1. ADA Bathroom

Lighting

1. Overhead LED lighting
2. Wall-mounted emergency lights per code.

Telephone & Cable:

Conduit provided to each unit – Owner/Tenant to contract with service provider to run service to unit.

Ceiling Height:

Clear heights range from approximately 17' to 30'.

NOTE: All preceding information is contingent upon approval by local jurisdiction having authority.

Buyer _____

Seller _____