

LINE TABLE		
LINE	BEARING	DISTANCE
L1	S42°07'41"W	18.50'
L2	S47°52'19"E	40.00'
L3	N42°07'41"E	215.85'
L4	N42°00'50"E	17.09'
L5	S48°10'33"E	166.32'
L6	S00°00'00"E	22.38'
L7	S41°52'59"W	155.61'
L8	N48°08'34"W	141.15'
L9	S41°50'06"W	289.08'
L10	N47°52'19"W	90.14'
L11	N41°51'27"E	198.64'
L12	N41°49'27"E	254.78'

CURVE TABLE					
NO.	DELTA	RADIUS	LENGTH	CHORD BEARING	CHORD DIST.
C1	003°47'52"	640.00'	42.42'	N40°13'45"E	42.41'
C2	030°17'10"	85.00'	44.93'	S15°08'35"W	44.41'
C3	090°16'49"	30.00'	47.27'	N86°59'34"E	42.53'

Parcel Exhibit ~ 1.353 Ac.

Village of Sunbury, Delaware County, Ohio
Farm Lot 8, Section 1, Township 4, Range 17
United States Military Lands

Bearings are based on the Ohio State Plane Coordinate System, North Zone, NAD83 (NSRS2007). Said bearings were derived from GPS observation and determine a portion of the existing centerline of U.S. Route 36/State Route 37 as having a bearing of S47°52'19"E.

This exhibit is based on existing records from Delaware County Auditor's and Recorder's records and an actual field survey completed in January, 2018.

All iron pins set are 5/8" diameter rebar, 30" long iron pipe with plastic cap inscribed "Advanced 7661".

Douglas R. Hock, P.S. 7661 Date:

DRAWN BY: BCK JOB NO.: 17-0026-149
DATE: 5/12/2020 CHECKED BY: DRB



422 Beecher Road
Gahanna, Ohio 43230
ph 614.428.7750
fax 614.428.7755

