



FIRST FLOOR PLAN

- NOTES:
1. FIRESTOP IN LOCATIONS SPECIFIED IN SOGA 921.0.
 2. UNLESS OTHERWISE NOTED, ALL NEW INTERIOR WALLS TO BE 5/8" THICK - METAL STUD AT 24" O.C. - W/ SOUND ATTENUATION BULKHEADS - EXTEND WALLS ABOVE RATED CUR. AS REQ'D
 3. SHADED AREAS INDICATE EXISTING CONSTRUCTION TO REMAIN (TYP.).
 4. FIRERETARDANT TREATED WOOD BLOCKING TO BE INSTALLED IN METAL STUD WALLS AT INTERVALS APPROPRIATE FOR HANGINGS OF MARKER BOARDS, TACK BOARDS, ETC. (ONLY WALLS INDICATED).
 5. CONTRACTOR TO VERIFY EXISTING FREEDER DUST CONDITIONS. TRENCH IS TO BE FILLED. CONSULT W/ ARCH. AFTER EXISTING CONDITIONS ARE EXPOSED - PRIOR TO PROCEEDING W/ WORK.
- ACCESSIBLE PARKING NOTES:
- PROVIDE 2 ACCESSIBLE PARKING SPACES AT CLOSEST LOCATION TO FRONT ENTRY:
1. VAN ACCESSIBLE SPACE - 8'-0" WIDE W/ AN ADJACENT 5'-0" ACCESS AISLE. FOLEY MOUNT & 1'-0" x 1'-6" INTERNATIONAL SYMBOL OF ACCESSIBILITY SIGN W/ VAN ACCESSIBLE SIGN MOUNTED BELOW. 5" MIN. CHARACTER
 2. ACCESSIBLE SPACE - 8'-0" WIDE W/ AN ADJACENT 5'-0" ACCESS AISLE. FOLEY MOUNT & 1'-0" x 1'-6" INTERNATIONAL SYMBOL OF ACCESSIBILITY SIGN. 5" MIN. CHARACTER



SCALE: 3/16" = 1'-0"

DATE: 1-12-92

REVISIONS:

7.28.92

SHEET:

A4

OF: 11