

611 New Orpheum Building
Los Angeles
November 19, 1929.

Mr. H. P. Stolz,
9th Floor, Pacific Electric Building,
Los Angeles, California.

Agent, Sunset Pacific Oil Company.

Dear Sir:

Your report of abandonment of well No. "Athens" 8,
Sec. 7, T. 3 S., R. 13 W., S. E. B. & M., Rosecrans oil
field, Los Angeles County, dated November 6, 1929, and sub-
mitted to this division on our form 102, has been examined
in conjunction with records filed in this office.

A review of the reports and records shows that the
requirements of this division, which are based on all
information filed with it, have now been fulfilled.

Yours truly,

R. D. Bush

State Oil and Gas Supervisor

By

[Signature]
ty Supervisor.

VJC:EMP

CC - Mr. H. D. Bush

11 8579

Date	Number	Cross Ref/Use	Cards	Pages	
				178	171
11/30	C. L. B.				✓

037-14456

CALIFORNIA STATE MINING BUREAU

Department of Petroleum and Gas

CALIFORNIA STATE MINING BUREAU
(REGISTRATION DIVISION)

NOTICE OF INTENTION TO DRILL NEW WELL

APR 13 1925

Department of Petroleum and Gas
LOS ANGELES, CALIFORNIA.

Crown Central Petroleum Corp.

This notice must be given before drilling begins

Los Angeles

Cal. April 11, 1925

Mr. C. C. Thoms.

Deputy State Oil and Gas Supervisor

Los Angeles.

Cal.

DEAR SIR:

In compliance with Section 17, Chapter 718, Statutes of 1915, as amended, notice is hereby given that it is our intention to commence the work of drilling well number 7 T 3 S R 13 W S.B. Rosecrans Oil Field, Los Angeles B. & M.,

perpendicularly to Laconia Blvd. Athens County.

The well is 35 feet N. of S. and 44 feet E. of N.W. corner Lot 15, Block 19 Tract Athens
(Give location in distance from section corners or other corners of legal subdivision)

The elevation of the derrick floor above sea level is 197.89 feet. (Elevation Later) U.S.G.S. Datum

We propose to use the following strings of casing either cementing or landing them as here indicated:

Harry Stolz by pho. 4-27-25 H.A.

Size of Casing, Inches	Weight, Lb. Per Foot	New or Second Hand	Depth	Landed or Cemented
15"	Stovepipe	New	<u>±</u> 800	Cemented.
10" or 8 1/4"		New	<u>±</u> 4200	Cemented.

It is understood that if changes in this plan become necessary we are to notify you before cementing or landing casing.

We estimate that the first productive oil or gas sand should be encountered at a depth of about 7 4200 feet, more or less.

Athens Division

Address 525 Laconia Blvd.

Telephone number Thornwall 5411

Respectfully yours,

JULIAN PETROLEUM CORPORATION.

(Name of Company or Operator)

By A. P. Stolz
Resident Engineer - Athens Division.

Address notice to Deputy State Oil and Gas Supervisor in charge of district where well is located
Reference to file of 2512

Date	Time	Class	Section	Cards	Forms	
					113	111

Handwritten notes and signatures at the bottom of the page, including dates like 4-13-25 and 4-27-25.

CALIFORNIA STATE MINING BUREAU
DEPARTMENT OF PETROLEUM AND GAS

Report on Proposed Operations

No. P. -1-10709

Los Angeles, Cal. May 5, 1925

Mr. E. H. Broughton,

Los Angeles, Cal.

Agent for JULIAN PETROLEUM CORPORATION ~~INCORPORATED~~

DEAR SIR:

Your.....proposal to drill Well No. "ATHENS" 8,
Section 7, T. 3, R. 13, S.B. B. & M., Rosecreans Oil Field, Los Angeles County,
dated April 11, 1925, received April 13, 1925, has been examined in conjunction with records filed in this office.

Present conditions as shown by the records and the proposal are as follows:

THE NOTICE STATES:

"The well is 35 feet S. and perpendicular to Laconia Blvd. and 44 feet E. from N. W. corner Lot 15, Block 18, Athens Tract.

The elevation of the derrick floor above sea level is 187.89 feet, U.S.C.S.

We estimate that the first productive oil or gas sand should be encountered at a depth of about 4200 feet, more or less."

PROPOSAL:

"We propose to use the following strings of casing either cementing or landing them as here indicated:

Size of Casing.	Weight.	New or Second Hand.	Depth.	Landed or Cemented.
16"	Stovepipe	New	± 800	Cemented.
10" or 8 $\frac{1}{4}$ "		New	± 4200	Cemented.

It is understood that if changes in this plan become necessary we are to notify you before cementing or landing casing."

RECOMMENDATION:

Available data indicate the following at this location:

1. Possible oil zone 3950' to 4150'.
2. Probable oil zone 4150' to 4350' or deeper.

THE PROPOSAL IS APPROVED WITH THE FOLLOWING RECOMMENDATIONS:

1. The well should be cored carefully starting at about 3950' or 10"
2. This department shall be consulted in regard to the cementing depth for the 8 $\frac{1}{4}$ " casing, after coring to locate the top of the oil zone, and before drilling below a depth of 4200'. or 10"
3. Effective mudding of the formations to be left back of the 8 $\frac{1}{4}$ " casing shall be demonstrated by circulating mud fluid through the drill pipe, hanging just off bottom after drilling and reaming to the cementing depth for this casing, until the loss is not more than 5.0 bbl. per hr.

KINDLY NOTIFY THIS DEPARTMENT TO WITNESS:

1. Final mudding operations before cementing the 8 $\frac{1}{4}$ " casing. or 10"
2. A bailing test of the 8 $\frac{1}{4}$ " shut-off.

NOTE: The issuance of this report was delayed pending receipt of elevation of well. This information was received April 27, 1925 by telephone from Mr. H. P. Stolz, your engineer.

cc-H. P. Stolz.

R. D. BUSH,

State Oil and Gas Supervisor

By C. C. Johnson Deputy

EPM:StA.

CALIFORNIA STATE MINING BUREAU

DEPARTMENT OF PETROLEUM AND GAS

CALIFORNIA STATE MINING BUREAU

RECEIVED

DEC 11 1925

Department of Petroleum and Gas

LOS ANGELES

Notice of Intention to Abandon Well

This notice must be given at least five days before work is to begin

Los Angeles, Cal. December 1st 1925.

Mr. E. Huegenin, Deputy State Oil and Gas Supervisor, Los Angeles, Cal.

DEAR SIR:

In compliance with Section 16, Chapter 718, Statutes of 1915, as amended, notice is hereby given that it is our intention to abandon well number Athens #8, Section 7, T. 3 S., R. 13 W., S.B. B. & M., Rosecrans Oil Field, Los Angeles County, commencing work on the 5th day of December, 1925.

The present condition of the well is as follows:

- 1.- 16" stovepipe cemented 760'.
2.- 10", 45# National D.B.X. casing cemented 4240': water not shut off.
3.- 10" casing shot and drilled out of at about 4180', sidetracking the following: 2 joints of 4" drill pipe, drill collar and fish tail bit, and 1 joint of 6 1/2" wash pipe (6 1/2" washpipe is over 4" drill pipe and the top of same is 5' above the shoe of the 10" casing (4235); top of 4" drill pipe is 20' above top of 6 1/2" washpipe (42150).
4.- Sidetracked all of above junk to 4533'; twisted off four stands and double of 5" drill pipe, 5" drill collar, 4" drill collar and fish tail bit. Top of fish at 4207'.
5.- Put in cement plug from unknown depth to 4100'. Cleaned out hard cement to 4120'.
6.- 10" casing bad (collapsed) at 1157'.

The proposed work is as follows:

- 1.- Fill hole with heavy mud, cap the top of the 10" and 16" casings, and abandon.

Therwell 5411

Called Broughton on 12/11/25... H

Abandon

Respectfully yours,

JULIAN PETROLEUM CORPORATION

(Name of Company or Operator)

By: A.P. Stop

Address notice to Deputy State Oil and Gas Supervisor in charge of district where well is located. Petr. Ener. Development Dept.