

629 South Hill Street
Los Angeles, California
October 30, 1931.

RECEIVED GENERAL SUPERVISOR
FOR PETROLEUM DIVISION

Mr. B. E. Parsons,
1003 Higgins Building,
Los Angeles, California.

Agent for General Petroleum Corporation of California.

Dear Sir:

Your report of abandonment of well No. "Collier" 13, Sec. 7, T. 3 S., R. 13 W., S. B. B. & M., Rosecrans oil field, Los Angeles County, dated October 20, 1931, and submitted to this Division on our form 102, has been examined in conjunction with records filed in this office.

A review of the reports and records shows that the requirements of this Division, which are based on all information filed with it, have now been fulfilled.

Yours truly,

R. D. Bush
State Oil and Gas Supervisor

By *E. J. Quinn*
Deputy Supervisor.

CC - W. L. Borough
R. O. Swayse

Reference to file of this

R. D. Bush		Form	
40	off.		

WJC:EMS

B
mmB
11-5-31
10/31/31
10/31/31

CALIFORNIA STATE MINING BUREAU

Department of Petroleum and Gas

DEPARTMENT OF OIL AND GAS
RECEIVED
AUG 1 1931
LOS ANGELES, CALIFORNIA

Notice of Intention to Abandon Well

This notice must be given at least five days before work is to begin

Los Angeles Cal. July 27 1931

Mr. E. Huguenin
Deputy State Oil and Gas Supervisor
Los Angeles Cal.

DEAR SIR:

In compliance with Section 16, Chapter 718, Statutes of 1915, notice is hereby given that it is our intention to abandon well number #13 Collier Section 7 T. 3 R. 13 S.E. B. & M., Rosecrans Oil Field Los Angeles County, commencing work on the 1st day of August 1931

The present condition of the well is as follows:

CASING RECORD

16" stovepipe cemented at 790'
8-5/8" casing " " 4552'
6 1/4" " " " 5093'
3" " landed " 5214' Incl. 183 perf. Pulled from 5070'

TOTAL DEPTH 5232'

Last production for this well was in May 1931. In 9 days it made 20 bbls. of oil and cut 99.0%. It is not a commercial well.

The proposed work is as follows:

- 1. Plug with cement from 5232' to 5095', have plug witnessed and continue plug to 5060'.
2. Cut and pull 6 1/4" from 4500' and cap stub.
3. Cut and pull 8-5/8" from 750', cap stub and have cap witnessed.
4. Fill to surface, cap at surface and abandon in this condition.

NOTE: This work will be done by General Petroleum crew.

Respectfully yours.

cc: W. L. McLaine
W. L. Borough
C. M. Gravett
Files

General Petroleum Corporation of California
(Name of Company or Operator)

By [Signature]

STATE OF CALIFORNIA
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL AND GAS

Report on Proposed Operations

No. P. -1-23483

Los Angeles, Cal. August 5, 1931.

Mr. B. E. Parsons,

Los Angeles, Cal.

Agent for GENERAL PETROLEUM CORPORATION OF CAL. ~~COMPANY~~

DEAR SIR:

Your proposal to abandon Well No. "COLLIER" 13, Section 7, T. 3 S., R. 13 W., S. B. B. & M., Rosecrans Oil Field, Los Angeles County, dated July 27, 1931, received Aug. 4, 1931, has been examined in conjunction with records filed in this office.

Present conditions as shown by the records and the proposal are as follows:

Records in addition to, or at variance with those shown in the notice:

The 8-5/8" & 6 1/4" shut-offs were not tested.

THE NOTICE STATES:

"The present condition of the well is as follows:

CASING RECORD

16" stovepipe cemented at	790'
8-5/8" casing	" " 4552'
4 1/4" "	" " 5093'
3" "	landed " 5214'

Incl. 183 perf. Pulled from 5070'

TOTAL DEPTH 5232'

Last production for this well was in May 1931. In 9 days it made 20 bbls. of oil and cut 99.0%. It is not a commercial well."

PROPOSAL:

"The proposed work is as follows:

1. Plug with cement from 5232' to 5095', have plug witnessed and continue plug to 5060'.
2. Cut and pull 6 1/4" from 4500' and cap stub.
3. Cut and pull 8-5/8" from 750', cap stub and have cap witnessed.
4. Fill to surface, cap at surface and abandon in this condition.

NOTE: This work will be done by General Petroleum crew."

DECISION:

THE PROPOSAL IS APPROVED PROVIDED THAT THIS DIVISION SHALL BE NOTIFIED TO WITNESS the location and hardness of cement plug at 5095' and on the stub of the 8-5/8" casing.

cc-W. L. Borough
R. O. Swayze
WJC:OH

R. D. BUSH

State Oil and Gas Supervisor

By

Deputy

CALIFORNIA STATE MINING BUREAU
DEPARTMENT OF PETROLEUM AND GAS

Report on Proposed Operations

No. P. 1-11533

Los Angeles, Cal. September 11, 1925.

Mr. Walter H. Fisher.

Los Angeles, Cal.

Pres. ~~of~~ ^{of} WALTER H. FISHER CORPORATION ~~Company~~

DEAR SIR:

Your supplementary proposal to drill Well No. 13

Section 7, T. 3 S., R. 13 W., S.B. B. & M., Roscorans Oil Field, Los Angeles County,

dated Sept. 8, 1925, received Sept. 11, 1925, has been examined in conjunction with records filed in this office.

Present conditions as shown by the records and the proposal are as follows:

THE NOTICE STATES:

"The new conditions are as follows:

Location: Lot 13, block 18, Athens Tract, 30' N. and 40' E. of South and West lines.

Elevation: 186.30'

Depth: 4135' 9/10/25."

PROPOSAL:

"We now propose to continue drilling to the 4900 foot zone and core to determine proper depth to cement casing. Will set 9 1/4" casing.

We will notify you prior to cementing casing."

RECOMMENDATION:

Available data indicate that commercial production may be obtained from the so-called "Upper Oil Zone" at this location.

Your proposal to set the first water string at about 4900' is therefore not approved.

This department recommends the following if you desire to produce from the 4900' zone,

- (a) Drill to 4215'. Mud formations above 4215' by circulating mud fluid thru the drill pipe hanging just above 4215' until the mud loss is not more than 5 bbl. per hr.
- (b) Cement a water string at 4215'.
- (c) Drill out cement and make new hole to 4220'.
- (d) Test shut-off with hole open to 4220' in the regular manner.
- (e) When shut-off at 4215' is approved, drill well on to 4900' zone. Start coring at 4850' to determine proper cementing depth. Continue coring to not more than 4910'.
- (f) Mud formations between upper and lower oil zones by circulating mud fluid thru drill pipe hanging at about 4890' until the mud loss is not more than 2.0 bbl. per hr.
- (g) Cement water string at about 4890' forcing sufficient cement to reach up to 4200' behind the casing. When sufficient cement has been forced behind this casing to reach 4200', close in between upper and lower water strings at surface and pump as much additional cement into the formation as is possible.
- (h) Drill out cement and test shut-off in regular manner with hole open not more than 5' below the casing shoe.
- (i) When shut-off at 4890'+ is approved, complete well at about 4970'.

KINDLY NOTIFY THIS DEPARTMENT TO WITNESS:

- 1. Final mudding operations prior to cementing water string at 4215'.
- 2. Bailing test of water shut-off at 4215'.
- 3. Final mudding operations prior to cementing water string at 4890'.
- 4. Bailing test of water shut-off at 4890'.

cc- Walter H. Fisher Corp.

EHL:MC

R. D. BUSH,

State Oil and Gas Supervisor

By:  Deputy

STATE OF CALIFORNIA
DEPARTMENT OF NATURAL RESOURCES

DIVISION OF OIL AND GAS

Special Report on Operations Witnessed

No. T-1-23377

Los Angeles, Cal. October 7, 1931.

Mr. B. E. Parsons,

Los Angeles, Cal.

121

Agent for GENERAL PETROLEUM CORPORATION OF CALIF. ~~ROSECRANS~~

DEAR SIR:

Operations at your well No. "COLLIER" 13 Section 7, T. 3 S., R. 13 W., S. E. B. & M.,
Rosecrans Oil Field, in Los Angeles County, were witnessed by
R. P. Phillips, representative of the supervisor,
on Sept. 29, 1931. There was also present F. J. Miles, Driller,

Ed. Manifea, Tooldresser.

Casing Record 16" S.P. cem. 790'; 8-5/8" cem. 4552'; 6 1/4" cem. 5093'; 3" landed 5214',
perf. 5031'-5214', pulled from 5070'; T.D. 5232', plugged with cement 5232'-5059'.

The operations were performed for the purpose of testing the location and hardness of a cement plug
proposed to be placed from 5232' to 5059' in the process of abandonment.

and the data and conclusions are as follows:

THE INSPECTOR ARRIVED AT THE WELL AT 2:30 P. M., AND MR. MILES REPORTED THE FOLLOWING:

1. The hole was cleaned out to 5232'.
2. On September 29, 1931, 7 sacks of Santa Cruz cement was dumped at 5232'.
3. The top of the cement was located at 5059'.

THE INSPECTOR NOTED THAT the bailer could not be spudded below 5059' and brought up a sample of set cement.

The test was completed at 3:30 p. m.

THE LOCATION AND HARDNESS OF THE CEMENT PLUG AT 5059' ARE APPROVED.

cc-W. L. Borough
R. O. Swayze
RFP:OH

R. D. BUSH
State Oil and Gas Supervisor

By  Deputy

DIVISION OF OIL AND GAS

Special Report on Operations Witnessed

No. T-1-23397

Los Angeles, Cal. October 15, 1931.

Mr. B. E. Parsons,

Los Angeles, Cal.

Agent for GENERAL PETROLEUM CORPORATION OF CALIF. ~~COMPANY~~

DEAR SIR:

Operations at your well No. "COLLIER" 13 Section 7, T. 3 S., R. 13 W., S.E. B. & M.,
Rosecrans Oil Field, in Los Angeles County, were witnessed by
Alva M. Johnson, representative of the supervisor,
on October 8, 1931. There was also present A. L. Saulsbury, Driller, and
J. D. Ballew, Tooldresser.

Casing Record 16" S.P. cem. 790'; 8-5/8" cem. 4552', pulled from 765'; 6 1/2" cem. 5093',
pulled from 4015'; 3" landed 5214', perf. 5031'-5214', pulled from 5070'. T.D. 5232',
plugged with cement 5232'-5059', 4010'-3965' and 740'-721'.

The operations were performed for the purpose of testing the location and hardness of a cement plug
proposed to be placed on the stub of the 8-5/8" casing in the process of abandonment.

and the data and conclusions are as follows:

- THE INSPECTOR ARRIVED AT THE WELL AT 10:45 A. M., AND MR. SAULSBURY REPORTED THE FOLLOWING:
1. The 6 1/2" casing was pulled from 4015'.
 2. The hole was bridged from 4015'-4010' and on October 5, 1931, 9 sacks of Santa Cruz cement was dumped at 4010'. The top of the cement was located at 3965'.
 3. The 8-5/8" casing was pulled from 765'.
 4. The hole was bridged with timbers and rope to 740'. On October 7, 1931, 18 sacks of Santa Cruz cement was dumped at 740'. The top of the cement was located at 720'.

THE INSPECTOR NOTED THAT the bailer could not be spudded below 721' and brought up a sample of set cement.

The test was completed at 11:05 a. m.

THE LOCATION AND HARDNESS OF THE CEMENT PLUG AT 721' ARE APPROVED.

cc-W. L. Borough
R. O. Swayze
AMJ:OH

R. D. BUSH

State Oil and Gas Supervisor

By [Signature] Deputy

CALIFORNIA STATE MINING BUREAU
DEPARTMENT OF PETROLEUM AND GAS

COPY FILED
CALIFORNIA STATE MINING BUREAU
DEPARTMENT OF PETROLEUM AND GAS
SEP 11 1925
107 540

SUPPLEMENTARY NOTICE

Mobil Oil Corp.

Los Angeles, Cal. Sept. 8, 1925.

Mr. E. Huguenin

Deputy State Oil and Gas Supervisor

Los Angeles, Cal.

DEAR SIR:

Please be advised that our notice to you dated May 20, 1925

stating our intention to Drill well number #13 "Collier" 13
(Drill, deepen, redrill, abandon)

Sec. Lot 13, Blk 18, Athens Tract B. & M. Rosecrans-Athens Oil Field,

Los Angeles

County, must be amended on account of changed or recently

discovered conditions.

The new conditions are as follows:

Location: Lot 13, block 18, Athens Tract, 30' N. and 40' E. of South and West lines.

Elevation: 186.30

Depth: 4900' set 8 1/4" casing.

4135 - 9/10/25

We now propose

To continue drilling to the 4900 foot zone and core to determine proper depth to cement casing. Will set 8 1/4" casing.

We will notify you prior to cementing casing.

Enter as new well
~~Supp. Notice~~

Respectfully yours,

Walter H. Fisher Corp.
(Name of Company)

By Charles H. Young

Reference to file of data

No.	Date	Change	By	Initials

B. H. W. 9/11/25