

Wood Thornton, SIOR Senior Vice President, Principal +1 804 267 7221 wood.thornton@colliers.com Jimmy Martin, SIOR Senior Vice President +1 804 267 7218 jimmy.martin@colliers.com



10505-10529 NORTH PARK

Building 1

Up to 40,000 SF Available

10505 NORTH PARK CT - BUILDING 1 | BUILDING SPECS

Available SF	40,000 (can be divided)
Gross Dimensions	250' x 160'
Column Spacing	50' x 50' w/ 60' Speed Bay
Clear Height	28'
Entrances	5 glass entrances, one at each bay
Floor thickness/ rating specs	6" unreinforced slab over 10 mil vapor retarder, Ff=50 Fl=35
Sprinkler	ESFR
Truck Court Depth	144'

Rear Load
11 - 9 'x 10' insulated manual OH doors w/ bumpers and EOD levelers
2 - 12'-6" x 16' insulated manual drive-in doors
72 spaces (3 HCP)
12 - 6'-6" x 4'
Temporary high bay LED w/ motion sensors. Additional lighting included in TI Package
2,000 amp 3 phase, 4-wire service



10505-10529 NORTH PARK

Building 2

Up to 64,000 SF Available

10519 NORTH PARK CT - BUILDING 2 | BUILDING SPECS

Available SF	64,000 (can be divided)
Gross Dimensions	400' x 160'
Column Spacing	50' x 50' w/ 60' Speed Bay
Clear Height	28'
Entrances	8 glass entrances, one at each bay
Floor thickness/ rating specs	8 glass entrances, one at each bay 6" unreinforced slab over 10 mil vapor retarder, Ff=50 Fl=35
Floor thickness/	6" unreinforced slab over 10 mil vapor

Dock Configuration	Rear Load
Dock High Doors Installed	20 - 9' x 10' insulated manual OH doors w/
Ilistalleu	bumpers and LOD levelers
Drive in Doors/	2 - 12'-6" x 16' insulated manual drive-in
Ramps	doors
Car Parking	52 spaces (3 HCP)
Clerestory Windows	16 - 6'-6" x 4'
	Temporary high bay LED w/ motion
Lighting	sensors. Additional lighting included in TI Package
Power	2,000 amp 3 phase, 4-wire service



10505-10529 NORTH PARK

Building 3

19,250 SF Available

10529 NORTH PARK CT - BUILDING 3 | BUILDING SPECS

10323 1401(11117)	ci boilbilla 3 boilbilla 3i Ec3
Available SF	19,250 (single user)
Gross Dimensions	145' x 150'
Column Spacing	50' x 50'
Clear Height	24'
Entrances	1 glass entrance
Floor thickness/ rating specs	6" unreinforced slab over 10 mil vapor retarder, Ff=50 Fl=35
Sprinkler	ESFR
Truck Court Depth	145'+

Dock Configuration	Side Load
Dock High Doors Installed	3 - 9' x 10' insulated manual OH doors w/ bumpers and EOD levelers
Drive in Doors/ Ramps	2 - 12'-6" x 16' insulated manual drive-in doors
Car Parking	27 spaces (1 HCP)
Clerestory Windows	9 - 6'-6" x 4'
Lighting	Temporary high bay LED w/ motion sensors. Additional lighting included in TI Package
Power	400 amp 3 phase, 4-wire service







