

ZONING

179 Attachment 1

Town of Queensbury

Table 1: Table of Area Requirements
 [Amended 1-28-2011 by L.L. No. 2-2013; 3-18-2013 by L.L. No. 2-2013; 12-16-2013 by L.L. No. 7-2013; 10-6-2014 by L.L. No. 5-2014; 4-18-2016 by L.L. No. 3-2016; 10-17-2016 by L.L. No. 7-2016; 2-27-2017 by L.L. No. 3-2017; 6-1-2020 by L.L. No. 6-2020]

District	Symbol	Minimum Lot Size (acres)	Density	Minimum				Minimum Setbacks				Merchandise Display ⁷ (feet)	Minimum Percent Permeable	Maximum Building Height Proposed (feet)	Floor Area Ratio (FAR)	Notes
				Lot Width ¹ (feet)	Road Frontage (feet)	Depth (feet)	Water Frontage (feet)	Area for Clustering (acres)	Front (feet)	Side (feet)	Rear (feet)					
Land conservation	LC-42A	42		400	400	—	400	210	100	100	200	95%	35			
	LC-10A	10		400	400	—	400	50	100	100	200	95%	35			
	PR-42A	42		400	400	800	800	210	100	100	150	90%	35			
	RR-5A	5		400	400	—	200	25	100	75	75	75%	40/35 ²			
Rural residential	RR-3A	3		400	400	—	200	15	100	75	100	75%	40/35 ²			
	WR	2		150	150	—	150	4	30	25, 20, 15, 12; varies with lot width ¹⁰	30	75%	28 ⁹	0.22		
Moderate-density residential	MDR	2 or 1 ³		100	100	—	100	2	30	25	30	50%	40/35 ²			
Neighborhood residential	NR	0.5 or 10,000 sf ⁴		50	50		50		20	100 ⁵	15	35%	40/35 ²			
Recreation commercial	RC	15,000 sf ⁶		75	75		200		30	20	20	30%	35			
Commercial moderate	CM	1		150	50	200	150	NA	75	20 minimum; sum 50	25	30%	40	0.3		
	CI	1		150	50	200	150	NA	75	20 minimum; sum 50	25	30%	40	0.3		
Commercial intensive	CI-18	1		150	50	200	NA	NA	50-100 ¹¹	20 minimum; sum 50 ¹⁸	25	30%	40-70 ¹¹			30% landscaped
	O			250	75		80		75	25	25	35%	40			15% landscaped
Commercial Intensive – Exit 18 Office																
Neighborhood commercial	NC			50	50	100	75		40	20	15	30%	30			
	MS			50	50		75		40-100 ¹³	0 ¹⁴	10	5%-10% varies with lot size ¹⁵	40 ¹⁶			5% landscaped ¹⁷
Commercial Light Industrial	CLI			200	100	200	200		50	30	30	30%	60			40,000 square feet Total building size cap for retail use only

QUEENSBURY CODE

District	Symbol	Minimum Lot Size (acres)	Density	Minimum						Minimum Setbacks				Minimum Building Height Proposed (feet)	Minimum Percent Permeable	Floor Area Ratio (FAR)	Notes
				Lot Width ¹ (feet)	Road Frontage (feet)	Depth (feet)	Water Frontage (feet)	Area for Clustering (acres)	Front (feet)	Side (feet)	Rear (feet)	Shoreline (feet)	Merchandise Display ⁷ (feet)				
Light Industrial Veteran's Field	LI-VF	1				200	200	NA	50	20	20	75		30%	35	0.3	
Heavy industry	HI		3 acres minimum per principal use or structure	300	300	400	200	NA	100	50	50	200		30%	50		
Enclosed shopping center	ESC	2.5	Maximum residential density as per § 179-3-040B(1)(b) [12] ²⁰	500	75		200	NA	40 ²¹	30 ²¹	30 ²¹	150 ²¹		20%	70 ¹⁹		15% minimum landscaped

NOTES:

- Minimum lot widths require compliance with access management requirements for shared driveways or double lot width.
- Thirty-five-foot building height applies within the Adirondack Park.
- Two acres of land per residential unit if not connected to public sewer and water systems; one acre of land per residential unit if connected to public water and sewer systems.
- Five-tenths acre of land per residential unit if not connected to public sewer and water systems; 10,000 square feet of land per residential unit if connected to public sewer and water systems.
- Ten feet if buildings not connected or zero if connected.
- With a minimum of 15,000 square feet of land per 2,000 square feet of floor area.
- Setback from the edges of pavement.
- Accessory structures shall have a maximum height of 16 feet.
- Seventy-five-foot setback applies to lands in the Rural Use classification in the Adirondack Park. See Zoning Map.
- See § 179-3-040A(5)(b)[3].
- A building setback greater than the minimum requirement of 50 feet may allow for a building height greater than the maximum of 40 feet otherwise allowed. See § 179-3-040B(8)(b)[2] and [9].
- See §§ 179-3-040B(5)(b)[9], 179-3-040B(5)(b)[10], and 179-7-070A(1)(c).
- Buildings shall occupy a minimum of 60% of the build-to lot width as measured by the building facade width divided by the build-to lot width. See § 179-3-040B(5)(b)[3].
- See § 179-3-040B(5)(b)[10] and 179-3-040B(5)(b)[11].
- See § 179-3-040B(5)(b)[9].
- See § 179-3-040B(5)(b)[11].
- Parcels adjacent to residential uses shall require a minimum fifty-foot setback which shall include at least a twenty-five-foot vegetated buffer.
- Buildings in excess of 40 feet in height shall have a front setback of 100 feet or greater.
- The maximum gross building residential area (total unit square footage) shall be 30% of the total building floor area of all other commercial buildings within the ESC zoning district. See § 179-3-040B(1)(b)[12].
- Back lots to be utilized for (1) mail anchor stores greater than 30,000 square feet each; and (2) multifamily dwelling; may be subdivided without otherwise required setbacks or frontage on a public road. See § 179-3-040B(1)(d).