

+ HEATER NAT GAS FORCED AIR

@ AIR DUCTS TO OWNER STORAGE

(S)
SMOKE & CO
COMBO DET.
BATTERY PWR

HATCH TO CRAWL SPACE 5'
MECHANICAL SPACE

- NG FURNACE & NG WH
- METERS G/E/W
- SMOKE AND CO DET BATTERY PWR

__._

FORMER MASONRY OPENINGS FRAMED IN WITH STUDS AND 5/8" DRYWALL

:

FRIDGE

GAS OVEN

Λ SINK

NOTE: STAIRS TO UPPER UNIT

SCHEDULE OF WINDOWS AND DOORWAYS/OPENINGS

A-36" DOORWAY/OPENING

B-32" DOORWAY/OPENING

C-24" DOORWAY/OPENING

D-30" DOORWAY/OPENING

E- 60" DOORWAY/OPENING

F- 28" DOORWAY/OPENING

G-WINDOW REMOVED - FRAMED, INSULATED, FINISHED PAINTED 5/8" PT PLY EXT, PAINTED 5/8" DRYWALL INT.

H- 26.5"W x 53"H WINDOW (4 SF EGRESS)

I- 30"W x 53"H WINDOW (4.5 SF EGRESS)

J- 32" DOOR, 1-3/8" SOLID CORE, SELF-CLOSING

K- 36" DOOR, 1-3/8 SOLID CORE, SELF-CLOSING