CHAPTER 534. - MIXED USE-II

Sec. 534.001. - Purpose.

The purpose of the Mixed Use-II (MU-II) zone is to identify allowed uses, establish development standards that promote pedestrian-oriented development in vibrant mixed-use districts, and encourage a mix of compatible uses in multi-story buildings.

(Eng. Ord. No. 4-18, § 3, 8-13-2018, eff. 9-12-2018)

Sec. 534.005. - Definitions.

Unless the context otherwise specifically requires, as used in this chapter, the following mean:

Pedestrian amenities means areas and objects that are intended to serve as places for public use and are closed to motorized vehicles. Examples include plazas, sidewalk extensions, outdoor seating areas, and street furnishings.

Primary street means a street that is classified in the Salem Transportation System Plan (TSP) as an arterial or collector.

Secondary street means a street that is classified in the TSP as a local street.

(Eng. Ord. No. 4-18, § 3, 8-13-2018, eff. 9-12-2018)

Sec. 534.010. - Uses.

(a) The permitted (P), special (S), conditional (C), and prohibited (N) uses in the MU-II zone are set forth in Table 534-1.

TABLE 534-1 USES

Table 534-1: Uses		
	Status	
Household Living		

about:blank Page 1 of 34

Single family	P	The following single family activities: ■ Townhouse. ■ Residential home, as defined under ORS 197.660. ■ Single family, when located in a mixed-use building.
	N	All other single family.
Two family	Р	Two family, when located in a mixed-use building.
	N	All other two family.
Three family	Р	
Four family	Р	
Multiple family	Р	
Group Living		
Room and board	Р	 The following room and board activities: Single-room occupancy. Other room and board serving 5 or fewer persons.
	С	Other room and board serving 6 to 75 persons.
	N	All other room and board.
Residential care	Р	The following residential care activities:

about:blank Page 2 of 34

		 Residential facility, as defined under ORS 197.660. Assisted living.
	N	All other residential care.
Nursing care	N	
Lodging		
Short-term commercial lodging	P	
Long-term commercial lodging	N	
Non-profit shelters	Р	Non-profit shelters serving 5 or fewer persons.
	С	Non-profit shelters serving 6 to 75 persons.
	N	All other non-profit shelters.
Retail Sales and Services		
Eating and drinking establishments	P	
Retail sales	Р	
Personal services	Р	
Postal services and retail financial services	P	

about:blank Page 3 of 34

Business and Professional Services		
Office	Р	
Office	'	
Audio/visual media production	P	
production		
Laboratory research and	P	
testing		
Motor Vehicle, Trailer, and M	lanufactur	ed Dwelling Sales and Service
Motor vehicle and	N	
manufactured dwelling and		
trailer sales		
Motor vehicle services	N	
Commercial parking	N	Standalone surface parking lots
	Р	All other commercial parking
Park-and-ride facilities	P	Park-and-ride facilities, when converted from
		portions of existing off-street parking areas.
	N	All other park-and-ride facilities.
Taxicabs and car services	N	
Heavy vehicle and trailer	N	
sales		

about:blank Page 4 of 34

Heavy vehicle and trailer service and storage	N	
Recreation, Entertainment, a	and Cultura	al Services and Facilities
Commercial entertainment	N	Firing ranges
—Indoor	Р	All other commercial entertainment—Indoor.
Commercial entertainment —Outdoor	N	
Major event entertainment	N	
Recreational and cultural community services	P	
Parks and open space	Р	
Non-profit membership assembly	P	
Religious assembly	Р	
Health Services		
Medical centers/hospitals	N	
Outpatient medical services and laboratories	Р	
	Status	

about:blank Page 5 of 34

Educational Services		
Day care	P	
Basic education	Р	
Post-secondary and adult education	Р	
Civic Services		
Government services	Р	
Social services	Р	
Governmental maintenance services and construction	N	
Public Safety	•	
Emergency services	Р	
Detention facilities	N	
Military installations	N	
Funeral and Related Services		
Cemeteries	N	
Funeral and cremation services	N	
	<u> </u>	

about:blank Page 6 of 34

Construction Contracting, Repair, Maintenance, and Industrial Services		
General repair services	Р	
Building and ground services and construction contracting	N	
Cleaning plants	N	
Industrial services	N	
Wholesale Sales, Storage, a	nd Distribu	tion
General wholesaling	N	
Heavy wholesaling	N	
Warehousing and distribution	N	
Self-service storage	N	
Manufacturing		
General manufacturing	P	General manufacturing, provided the manufacturing does not exceed 5,000 square feet of total floor area per development site and retail sales of the products manufactured is provided on-site.
	N	All other general manufacturing.

about:blank Page 7 of 34

Heavy manufacturing	N	
Printing	N	
Transportation Facilities		
Aviation facilities	N	
Passenger ground	Р	Transit stop shelters
transportation facilities	N	All other passenger ground transportation facilities.
Marine facilities	N	
Utilities		
Basic utilities	N	Reservoirs; water storage facilities; electric substation.
	Р	All other basic utilities.
Wireless communication facilities	Allowed	Wireless communication facilities are allowed, subject to SRC <u>chapter 703</u> .
Drinking water treatment facilities	N	
Power generation facilities	N	
Data center facilities	N	
Fuel dealers	N	

about:blank Page 8 of 34

N		
N		
N		
N		
al Services		
N		
N		
N		
N		
Р		
Other Uses		
Р	The following temporary uses: ■ Construction modular, subject to SRC 701.016. ■ Emergency shelter, subject to SRC 701.025. ■ Managed temporary village, subject to SRC 701.030. ■ Safe parking shelter, subject to SRC 701.041.	
	N N N Sel Services N N N P	

about:blank Page 9 of 34

Home occupations	S	Home occupations, subject to SRC <u>700.020</u> .
Accessory dwelling units	S	Accessory dwelling units, subject to SRC 700.007.

- (b) *Prohibited uses.* Notwithstanding Table 534-1, any permitted, special, or conditional use within the MU-II zone shall be a prohibited use if developed with a drive-through.
- (c) *Continued uses.* Existing, legally-established uses within the MU-II zone established prior to August 24, 2022, but which would otherwise be made non-conforming by this chapter, are hereby deemed continued uses.
 - (1) Buildings or structures housing a continued use may be structurally altered, enlarged, or rebuilt following damage or destruction, provided:
 - (A) Such alteration, enlargement, or rebuilding of a conforming development complies with the standards in this chapter; or
 - (B) Such alteration, enlargement, or rebuilding of a continued development complies with the standards set forth in SRC <u>534.015(g)</u>.
 - (2) A continued use shall terminate if the building or structure ceases to be occupied for that continued use for any reason for a continuous period of one year.
 - (3) Conversion of the building or structure to a conforming use shall thereafter prevent conversion back to the former continued use or any other continued use.

(Eng. Ord. No. 4-18, § 3, 8-13-2018, eff. 9-12-2018; Ord. No. 1-20, § 2(Exh. B), 2-24-2020; Ord. No. 13-21, § 1(Exh. A), 2-14-2022; Ord. No. 11-22, § 1(Exh. A), 7-25-2022, eff. 8-24-2022; Ord. No. 7-23, § 1(Exh. A), 11-27-2023; Ord. No. 8-24, § 1(Exh. A), 9-23-2024)

Sec. 534.015. - Development standards.

Development within the MU-II zone must comply with the development standards set forth in this section.

(a) Lot standards. Lots within the MU-II zone shall conform to the standards set forth in Table 534-2.

about:blank Page 10 of 34

TABLE 534-2 LOT STANDARDS

Table 534-2: Lot Standards		
Requirement	Standard	Limitations & Qualifications
Lot Area		
All Uses	None	
Lot Width		
All Uses	None	
Lot Depth		
All Uses	None	
Street Frontage		
All Uses	16 ft.	

- (b) *Dwelling unit density.* Development within the MU-II zone that is exclusively residential or single-room occupancy shall have a minimum density of 15 dwelling units per acre.
- (c) *Setbacks.* Setbacks within the MU-II zone shall conform to the standards set forth in Tables 534-3 and 534-4.

TABLE 534-3 SETBACKS

about:blank Page 11 of 34

Table 534-3: Setbacks		
Requirement	Standard	Limitations & Qualifications
Abutting Street		
Buildings		
All uses	0 ft. or Max. 10 ft.	(1) Maximum 10-foot setback applies if the setback area is used for pedestrian amenities.
		a) The maximum setback does not apply to a new building if another building exists between a minimum of 50 percent of the street-facing facade of the new building and the street. b) For double frontage lots, the setback abutting a street shall only apply to the street with the highest street classification or, where both streets have the same classification, the street designated by the applicant. No minimum or maximum setback is required abutting the other street.
		(2) A minimum setback of five feet to a maximum setback of 10 feet is permitted for ground-floor residential uses if horizontal separation is provided pursuant to SRC <u>534.015(h)</u> .
		a) The maximum setback does not apply to a new building if another building exists between a minimum of 50 percent of the street-facing facade of the new building and the street.

about:blank Page 12 of 34

		b) For double frontage lots, the setback abutting a street shall only apply to the street with the highest street classification or, where both streets have the same classification, the street designated by the applicant. No minimum or maximum setback is required abutting the other street.
Accessory Structures	5	
All uses	Min. 10 ft.	
Vehicle Use Areas	'	
All uses	Per SRC <u>chapter</u> 806	The use of a berm under 806.035(c)(2)(B) is prohibited.
Interior Front		
Buildings		
All uses	None	
Accessory Structures	'	
All uses	None	
Vehicle Use Areas	'	
All uses	Per SRC <u>chapter</u> 806	

about:blank Page 13 of 34

Interior Side		
Buildings		
All uses	Zone-to-	
	zone	
	setback	
	(Table 534-	
	4)	
Accessory Structi	ures	
All uses	Zone-to-	
	zone	
	setback	
	(Table 534-	
	4)	
Vehicle Use Areas	 S	
All uses	Zone-to-	
	zone	
	setback	
	(Table 534-	
	4)	
Interior Rear		
Buildings		

about:blank Page 14 of 34

All uses	Zone-to- zone setback (Table 534- 4)
Accessory Structures	
All uses	Zone-to- zone setback (Table 534- 4)
Vehicle Use Areas	
All uses	Zone-to- zone setback (Table 534- 4)

TABLE 534-4 ZONE-TO-ZONE SETBACKS

Table 534-4: Zone-to-Zo	one Setbacks	

about:blank Page 15 of 34

Abutting Zone	Type of Improvement	Setback	Landscaping & Screening
EFU	Buildings and accessory structures	None	N/A
	Vehicle use areas	Min. 5 ft. ⁽¹⁾	Туре А
Residential zone	Buildings and accessory structures	Min. 10 ft. plus 1.5 feet for each 1 foot of building height above 15 feet (2)	Type C
	Vehicle Use Areas	Min. 5 ft.	Type C
Mixed-use zone	Buildings and accessory structures	None	N/A
	Vehicle use areas	Min. 5 ft. ⁽¹⁾	Type A
Commercial zone	Buildings and accessory structures	None	N/A
	Vehicle use areas	Min. 5 ft. ⁽¹⁾	Type A
Public zone	Buildings and accessory structures	None	N/A
	Vehicle use areas	Min. 5 ft. ⁽¹⁾	Туре А
Industrial and	Buildings and accessory	None	N/A

about:blank Page 16 of 34

	Vehicle use areas	Min. 5 ft. ⁽¹⁾	Туре А
Limitations & Qualifications			

- (1) Zone-to-zone setbacks are not required abutting an alley.
- (2) The additional 1.5-feet for each 1-foot of building height above 15 feet does not apply abutting a creek.
 - (d) Lot coverage; height; building frontage. Buildings and accessory structures within the MU-II zone shall conform to the lot coverage, height, and building frontage standards set forth in Table 534-5.

TABLE 534-5
LOT COVERAGE; HEIGHT; BUILDING FRONTAGE

Table 534-5: Lot Coverage; Height; Building Frontage					
Requirement Standard Limitations & Qualifications					
Lot Coverage					
Buildings and Accessory Structures					
All uses	No Max.				
Rear Yard Coverage					
Buildings					

about:blank Page 17 of 34

All uses	NA				
Accessory Structures					
All uses	No Max.				
Height					
Buildings and Accessory St	ructures				
All uses	Max. 45 ft.	contig Histor standa that a	table to buildings on a lot or lots that are guous to a National Register Residential ric District. For the purposes of this ard, contiguous shall include a lot or lots re separated from a National Register ential Historic District by an alley.		
	Max. 55 ft.	Applic	able to buildings on all other lots.		
Building Frontage	Building Frontage				
Buildings					
All uses	Min. 50%	(1)	For corner lots, this standard must be met on the frontage of the street with the highest street classification. For the intersecting street, the building frontage standard is a minimum of 40%.		
		(2)	For corner lots where both streets have the same classification, the applicant may choose on which street to meet the		

about:blank Page 18 of 34

			minimum 50% building frontage standard and on which street to meet the minimum 40% building frontage standard.
		(3)	For double frontage lots, this standard must only be met on the street with the highest classification. Where both streets have the same classification, the applicant may choose on which street the building frontage standard shall apply.
Accessory Structures			
All uses	Not applicable	Accessory structures shall be located behind or beside buildings.	

- (e) *Parking.* Off-street parking shall not be located on a new standalone surface parking lot in the MU-I zone or MU-II zone.
- (f) Landscaping.
 - (1) Setback areas. Setbacks, except setback areas abutting a street that provide pedestrian amenities or horizontal separation pursuant to SRC <u>534.015(h)</u>, shall be landscaped. Landscaping shall conform to the standards set forth in SRC <u>chapter 807</u>.
 - (2) *Vehicle use areas.* Vehicle use areas shall be landscaped as provided under SRC <u>chapter 806</u> and SRC <u>chapter 807</u>.
- (g) *Continued development.* Buildings and structures existing within the MU-II zone on September 12, 2018, that would be made non-conforming development by this chapter are hereby deemed continued development. The owner shall have the burden to

about:blank Page 19 of 34

demonstrate continued development status under this subsection.

- (1) Single family uses.
 - (A) *Buildings*. Continued development housing a continued single family use may be structurally altered or enlarged, or rebuilt following damage or destruction, provided such alteration, enlargement, or rebuilding conforms to development standards of the Single Family Residential (RS) zone set forth in SRC <u>chapter 511</u> and to all other applicable provisions of the UDC, except for lot size and dimension standards in SRC <u>chapter 511</u>.
 - (B) Accessory structures. Existing accessory structures on the same property as a continued single family use may be structurally altered or enlarged, or rebuilt following damage or destruction, and new accessory structures to a continued use may be constructed, provided such alteration, enlargement, rebuilding, or new accessory structure construction conforms to the development standards of the Single Family Residential (RS) zone set forth in SRC chapter 511, except the lot size and dimensions standards, and to all other applicable provisions of the UDC.
 - (C) Option to rebuild in same location. Notwithstanding SRC <u>543.015(h)(1)(A)</u> and (B), any continued development housing a continued single family use or associated accessory structure rebuilt following damage or destruction may either be located on the same location on the lot as the original building or structure, or in compliance with the setbacks of the Single Family Residential (RS) zone set forth in SRC <u>511.010(b)</u>.
- (2) All other uses. Continued development, housing a use other than a continued single family use, may be structurally altered, enlarged, or rebuilt following damage or destruction, provided such alteration, enlargement, or rebuilding conforms to the following standards:
 - (A) *Minor alterations*. Exterior alterations to buildings that alter less than 20 percent of an existing building facade area facing a primary street are exempt from all of the development standards in this chapter. Such alterations shall not increase the building facade's nonconformity to the pedestrian-oriented design standards in Table 534-6.
 - (B) *Minor additions.* Additions to buildings that enlarge or alter an existing building facade area facing a primary street by less than 20 percent are exempt from all of the development standards in this chapter except for interior setbacks, parking,

about:blank Page 20 of 34

landscaping, and maximum height standards. Such additions shall not increase the building facade's nonconformity to the pedestrian-oriented design standards in Table 534-6.

- (C) *Major alterations.* Exterior alterations to buildings that alter between 20 percent and 60 percent of an existing building facade area facing a primary street shall decrease that building facade's nonconformity to all pedestrian-oriented design standards in Table 534-6 that are applicable to that alteration. Such alterations are exempt from all other development standards in this chapter.
- (D) *Major additions.* Additions to buildings that enlarge or alter an existing building facade area facing a primary street by between 20 percent and 60 percent shall:
 - (i) Comply with a minimum of three of the pedestrian-oriented design standards in Table 534-6; or
 - (ii) Comply with a minimum of one of the pedestrian-oriented design standards in Table 534-6 and add perimeter landscaping in vehicle use areas if such landscaping is not already required under SRC <u>534.015(f)</u>.

For the purposes of SRC <u>534.015(g)(2)(D)(i)</u> and (ii), the pedestrian-oriented design standards in Table 534-6 shall apply to the addition. Major additions must meet all other development standards in this chapter except for building frontage and maximum setback abutting a street.

- (E) Substantial alterations. Exterior alterations to buildings that alter more than 60 percent of an existing building facade area facing a primary street shall meet all applicable pedestrian-oriented design standards in Table 534-6. Such alterations are exempt from all other development standards in this chapter.
- (F) Substantial additions or redevelopment. Additions to buildings that enlarge or alter an existing building facade area facing a primary street by more than 60 percent shall meet all applicable development standards in this chapter. Continued development that is rebuilt following damage or destruction shall meet all development standards in this chapter.
- (G) *Accessory structure.* Alterations and additions to accessory structures shall meet all applicable development standards in this chapter.
- (h) *Pedestrian-oriented design.* Development within the MU-II zone, excluding development requiring historic design review, shall conform to the pedestrian-oriented design

about:blank Page 21 of 34

standards set forth in Table 534-6. Any development requiring historic design review shall only be subject to design review according to the historic design review standards or the historic design review guidelines set forth in SRC <u>chapter 230</u>.

TABLE 534-6
PEDESTRIAN-ORIENTED DESIGN

Requirement	Standard	Limitations & Qualifications
Ground Floor Height		
This standard applies to building ground floors on primary streets.	Min. 10 ft.	For the purposes of this standard, ground floor height is measured from the floor to the ceiling of the first floor.
	FIGURE GROUND FLO	
Mi	n 10'	

about:blank Page 22 of 34

This standard applies when a dwelling unit is located on the ground floor.	Vertical or horizontal separation shall be provided	For the purposes of this standard, separation is required between the public right-of-way and the residential entryway and any habitable room.
	Vertical Distance Min. 1.5 ft. Max. 3 ft.	Vertical separation shall take the form of several steps or a ramp to a porch, stoop, or terrace.
	Horizontal Distance Min. 5 ft. Max. 10 ft.	Horizontal separation shall take the form of a landscaped area such as private open space or hardscaped area such as a plaza.

FIGURE 534-2 HORIZONTAL SEPARATION



about:blank Page 23 of 34

Building Facade Articulat	ion		
This standard applies to building facades facing primary streets.	Required	(1)	For buildings on corner lots, where the primary street intersects with a secondary street, these standards shall apply to the full length of the front facade and the portion of the side facade that extends a minimum of 50 feet from the corner where the primary street meets the secondary street, or to the edge of the building or the lot, whichever is shorter.
		(2)	Buildings shall incorporate vertical and horizontal articulation and shall divide vertical mass into a base, middle, and top.
			a) Base: Ground floor facades shall be distinguished from middle facades by at least one of the following standards:
			1. Change in materials.
			2. Change in color.
			3. Molding or other horizontally- articulated transition piece.
			b) Middle: Middle facades shall

about:blank Page 24 of 34

	provide visual interest by incorporating at a minimum of every 50 feet at least one of the following standards:
	1. Recesses of a minimum depth of two feet.
	2. Extensions of a minimum depth of two feet.
	3. Vertically-oriented windows.
	4. Pilasters that project away from the building.
c)	Top: Building tops shall be defined by at least one of the following standards:
	1. Cornice that is a minimum of eight inches tall and a minimum of three inches beyond the face of the facade.
	2. Change in material from the upper floors, with that material being a minimum of eight inches tall.

about:blank Page 25 of 34

	3. Offsets or breaks in roof elevation that are a minimum of three feet in height.	
	4. A roof overhang that is a minimum of eight inches beyond the face of the facade.	
	The repainting of a facade of an existing building is exempt from this standard.	

FIGURE 534-3 ARTICULATION



Ground Floor Windows

This standard applies to building ground floors on primary streets. Residential uses Min. 30% (1) For the purposes of this standard, ground floor building facades shall include the minimum percentage of

about:blank Page 26 of 34