CUT CONCRETE FLOOR AS REQUIRED FOR NEW DRAIN LINE. REPAIR AND PATCH PER DETAIL 3/A401. REPAIR FLOOR FINISHES

INSTALL 18-INCH VERTICAL GRAB BAR

NEW DRINKING FOUNTAIN. SEE 3/A101

INSTALL 18-INCH VERTICAL GRAB BAR (TYPICAL EACH RESTROOM)

PROJECT LIMITS

RESTROOM
105

15" min.

ETR

3' - 8"

2' - 3 1/2"

4' - 8"

1' - 2"

3' - 8"

CLR

4' - 4 1/2"

10' - 8 1/4"

2

RELOCATE EXISTING LAV TO PROVIDE FOR REQUIRED FLOOR CLEARANCES

CHILDCARE
104

NO WORK

5' - 10"

6' - 5 3/8"

33' - 4 1/8"

EXISTING RAISED CHANCEL

1

CONTRACTOR SHALL CONFIRM THAT CHANCEL CONSTRUCTION MEETS REQUIREMENTS OF NCBC 410.4 (NON-COMBUSTIBLE CONSTRUCTION).

IF COMBUSTIBLE CONSTRUCTION IS PRESENT IT SHALL BE REMOVED AND REPLACED WITH STEEL OR FIRE RETARDANT WOOD FRAMING WITH FIRE RETARDANT WOOD DECKING, ALL CONCEALED SPACES SHALL BE PACKED SOLID WITH UNFACED BATT INSULATION

003

004

005

MEN
106

WOMEN
107

2
A101

KITCHENETTE
109

NO WORK

STORAGE
108

NO WORK

CLASSROOM
110

NO WORK

CORRIDOR
111

NO WORK

101c

ETR

16' - 5"

PROJECT LIMITS

CHILDCARE
103

NO WORK

SANCTUARY
101

EXISTING RAISED SOUND BOOTH

31' - 5 1/4"

PROJECT LIMITS

101b

13' - 0 3/4"

135.00°

CONFERENCE
102

NO WORK

11' - 9 7/8"

101a

14' - 5 1/8"

PROJECT LIMITS

26' - 2 7/8"

9' - 0"

LOBBY
100

MEETING ROOM
112

NO WORK

002

001

006

1 FLOOR PLAN

1/4" = 1'-0"