

## CONSUMER INSULATION INFORMATION

Home Manufacturer: Clayton

Model Sardo

Serial No. 25018

The above home contains the following insulation specifications:

The circled values reflect what is contained in this home:

LOCATION	TYPE OF INSULATION	*THICKNESS	"R" VALUE
Floor	Fiberglass	2.25" <u>3.50"</u> 4.50" 7"	R7 <u>R11</u> R14 R22
Exterior Walls	Fiberglass	<u>3.50"</u> (3.50"HP) 6.25"	<u>R11</u> (R13 HP) R19
Ceiling	Therm X Blown (Cellulose)	1.9" 3.8" <u>5.7"</u> 7.1" 3.0" 5.2" 6.8" 7.6" 8.2"	R7 R14 <u>R21</u> R26 R11 R19 R25 R28 R30
Ceiling	Fiberglass	3.50" 4.50" 6.75" 7" 8" 8.36"	R11 R14 R21 R22 R25 R26
Ceiling	Fiberglass Batt Roof Rumble	2.25"	R7

**Note:** Roof Rumble (when applicable) is an addition to existing ceiling "R" Value.

This insulation information was furnished by the home manufacturer and is disclosed in compliance with the Federal Trade Commission Rule, Labeling and Advertising of Home Insulation, 16 CFR Section 460.16.

Date: \_\_\_\_/\_\_\_\_/\_\_\_\_ RETAILER SIGNATURE \_\_\_\_\_

I hereby understand that a copy of this form will be included with my sales contract.

Date: \_\_\_\_/\_\_\_\_/\_\_\_\_ CUSTOMER SIGNATURE \_\_\_\_\_

\*Thickness as certified by original supplier of insulation.

\*Savings vary. Higher R-values mean greater insulating power.

REVIEWED AND APPROVED BY THE FEDERAL TRADE COMMISSION STAFF RESPONSIBLE FOR ENFORCEMENT OF THE RULE ON LABELING AND ADVERTISING OF HOME INSULATION.

JANUARY 27, 1983.