



E 02 SCALE: 18" = 1'-0"



AE 02 SCALE: 1/8" = 1'-0"

- | | |
|----|--|
| 3 | APPROXIMATE LINE OF GRADE |
| 2 | ABOVE GRADE EXPOSED FOUNDATION WALL |
| 4 | MASONRY OR TILE - |
| 5 | CONCRETE FOOTING AND FOUNDATION WALL AS REQUIRED PER LOCAL CODES |
| 6 | VINYL FIBRED WINDOW WITH THERMAL BROKEN FRAME, INSULATED GLAZING |
| 7 | ALUMINUM SLIDING ENTRY DOOR WITH THERMAL BROKEN FRAME AND INSULATED GLAZING |
| 8 | EXHAUST FAN - REFER TO MECHANICAL DRAWINGS |
| 9 | ALUMINUM SLIDING ENTRY DOOR W/ INSULATED GLAZING |
| 10 | PAINTED TILED STEEL CANOPY |
| 11 | FINISH CONTROL JOINT |
| 12 | TAMPER RESISTANT, RECESSED HOSE BIB - MOUNT PUT AT 12" A.F.F. |
| 13 | SIDING - REFER TO EXTERIOR SIDING SPECIFICATIONS |
| 14 | WYAR FINISH ALUMINUM COPIING SYSTEM - COLOR TO MATCH ADJACENT MATERIAL. |
| 15 | EXHAUST VENT - COLOR TO MATCH ADJACENT MATERIAL |
| 16 | EXPANSION JOINT @ FLOOR LINE W/ BACKER ROD AND SEALANT |
| 17 | ALUMINUM DOOR - COLOR TO MATCH ADJACENT MATERIAL MATCHING ADJACENT |
| 18 | BUILDING HEIGHT DIMENSIONS ARE BASED ON WOOD FRAME CONSTRUCTION. THESE DIMENSIONS WILL VARY BASED ON FINAL BUILDING CONSTRUCTION. INTERIOR CEILING HEIGHT DIMENSIONS ARE CRITICAL TO MAINTAIN AS MINIMUMS. |
| 19 | CONCRETE PAD - REFER TO AREA DEVELOPMENT PLAN |
| 20 | ACCESSIBLE KICK BOARD HEAD W/ ELECTRIC STRIKE IN DOOR - TOP OF READER AT 48" MAX. HEIGHT |
| 21 | MATCH THE DOOR COLOR TO ADJACENT WALL. |
| 22 | EXTERIOR INSULATED FINISH SYSTEM (EIFS) |
| 23 | CULTURE STONE |
| 24 | NOT USED |

ALL SIGNAGE SHOWN FOR ILLUSTRATIVE PURPOSES ONLY.
LOCATION, SIZE, ETC. TO BE DETERMINED ON AN INDIVIDUAL
PROJECT BASIS.

MINIMUM 3/4" PLYWOOD BACKBOARD REQUIRED AT SIGN
LOCATIONS. AREA SHOULD COVER ENTIRE LENGTH AND HEIGHT
OF FASCIA OR SPACE AVAILABLE FOR SIGN.

ELECTRICAL AND FINAL CONNECTION BY CONTRACTOR.
ELECTRICAL REQUIREMENTS MAY BE OBTAINED FROM SIGN
COMPANY. TYPICAL 120V REQUIREMENT

RACEWAYS/ WIREWAYS ARE NOT ALLOWED.

PERMANENT ACCESS DOORS TO INTERIOR OF ALL PARAPETS
WHERE SIGNS ARE LOCATED TO BE PROVIDED BY CONTRACTOR.
CONTRACTOR TO FURNISH AND CONNECT PRIMARY ELECTRICAL
SERVICE INSIDE PARAPET WALL.

GUESTROOMS OR PUBLIC SPACES WITH SIGNAGE ON EXTERIOR
WALLS MUST HAVE ELECTRICAL PENETRATIONS AND/OR
INSTALLED PRIOR TO CLOSING UP THE WALL. PENETRATION
LAYOUT MAY BE OBTAINED FROM SIGN COMPANY.

Best Western Plus
Northlake Lodging Development inc
820 South I 35 E 102

Best Western Plus
Executive Residency
13860 Elizabethtown Cemetery road
North Lake Texas-76262



Drawn By: CP
Checked By: RA
Issue Date:
Project No:

Sheet Information:
EXTERIOR
ELEVATIONS
Sheet No:

A5.02