ADAMATIC

ADAMATIC

ADAMATIC

RESET
Model No:
Serial No:
Input Rating:
Gas Natural
Manifold Pressure:
Electric Features:
Blower Motor 208-230/460 VAC
60 Hz 3 Phase
4.6 RLA , 3 HP
Control Circuit:
115 VAC 60 Hz 1 Phase 7.4 Amps
Rotator Motor: 208-230/460 VAC
60 Hz 3 Phase
0 RLA 1/3 hp
Remote Motors: 5.4 amps maximum
Minimum circuit ampacity: 15 Amps
Maximum overcurrent device size: 20 Amps
CAUTION:
This appliance has more than one power supply connection point.
Disconnect all power supplies before servicing.
For use only on non-combustible floors.
Not suitable for connection to type B vent before draft inducer motor on combustion air.
Minimum clearances from combustible construction:
Zero inches from sides and back.
Twenty-four inches from top
Intended for other than household use.
Adamatic
607 Industrial Way West
Eatontown, N.J. 07724
Phone: 732-544-8400
Fax: 732-544-8420
Toll Free: 800-526-2007
Fax: 732-544-8420
Website: www.adamatic.com

ON
OFF
TEMP
HUMIDITY
TIMER
NUMBER
TIMERS

CAUTION
SLIPPERY
WHEN WET
ATTENTION
BAXTER
ADAMATIC

APOMATIC

BOHN