


# GENERAL NOTES

1. ALL DIMENSIONS ARE TO FACE OF STUD.
2. CONTRACTOR SHALL VERIFY LAYOUT DIMENSIONS PRIOR TO FRAMING. NOTIFY ARCHITECT OF ANY DISCREPANCIES.
3. FINISHES ARE TO BE SELECTED BY OWNER AND SHALL MEET CODE REQUIREMENTS FOR FLAME SPREAD AND MOISTURE RESISTANCE.
4. ALL PENETRATIONS THROUGH FIRE RATED ASSEMBLIES SHALL BE INSTALLED TO PRESERVE U.L. RATING REQUIREMENTS.
4. CONTRACTOR SHALL FOLLOW GUIDELINES ESTABLISHED BY THE LANDLORD.

# FINISHES

- OFFICE WALLS - GYP. BD. , TAPE, BED, NO TEXTURE - PRIME AND FLAT WALL PAINT TO COVER
- RESTROOM WALLS - CERAMIC TILE TO 48" A.F.F - GYP. BD. TO CEILING - TAPE, BED NO TEXTURE - PRIME AND PAINT LATEX ENAMEL TO COVER
- OFFICES/CORRIDORS FLOOR & BASE - DIRECT GLUE-DOWN CARPET SELECTED BY OWNER W/ALKYD BASE PAINTED MDF OR WOOD BASE.
- RESTROOM FLOOR & BASE - CERAMIC TILE COLOR/PATTERN SELECTED BY OWNER
- RECEPTION FLOOR & BASE - DIRECT GLUE-DOWN CARPET SELECTED BY OWNER W/ALKYD BASE PAINTED MDF OR WOOD BASE.
- OFFICES & CORRIDOR CEILINGS - 5/8" MINERAL FIBER BD.TILE W/ WHITE FISSURD FINISH IN WHITE 2X4 SUSPENDED CEILING GRID SYSTEM
- RECEPTION CEILING - 5/8" GYP. BOARD, TAPE & BED NO TEXTURE ON 2X4 SUSPENDED CEILING GRID SYSTEM PRIME AND PAINT FLAT WALL, COLOR SELECTED BY OWNER

# TYPICAL DOOR



3080 SOLID CORE MASONITE SLAB DOOR  
 IN RACO CLEAR ANODIZED ALUMINUM FRAME  
 BRUSHED STAINLESS STEEL LEVER LATCHSET HARDWARE & HINGES