

C. *Urban neighborhood (UN).*

1. *Principal building placement.*

- a. The front building facade shall be constructed parallel to the street along the front property line with a required setback of not less than ten feet.
- b. The side setbacks are not less than five feet on each side.
- c. The rear setback shall be not less than 15 feet.
- d. The front street facade width of the principal building shall not be less than 60 percent of the lot width.

2. *Principal building height.*

- a. The maximum building height is three stories and 35 feet.
- b. There is no major Urban Code conditional use available for an additional story or building height in this subdistrict.

3. *Parking.*

- a. Parking areas shall be located as follows:

- i. For new development, all parking areas shall be located behind the rear facade of a principal building or screened from public rights-of-way by a streetwall, other screening approved by the city development director, or landscape buffer as described in section [6.04.00, Landscaping](#), of this Code.
 - ii. For substantial renovation, parking areas shall be located, where possible, behind the rear building facade or at the side property line and screened from public rights-of-way by a streetwall, other screening approved by the city development director, or landscape buffer as described in section [6.04.00, Landscaping](#), of this Code.

4. *Architectural requirements.*

- a. Porches are required on the front building facade. Porches shall have a minimum depth of six feet and a minimum length of 70 percent of the building width. On corner properties, porches must be constructed along both street facades. Porches may project two feet into the front setback.
- b. Walls, wood picket fences, wrought iron fences, or hedges are required along the front property line and on corner lots, along the side property lines and shall have a minimum height of three feet and a maximum height of four feet along the front and side property lines to the front facade of the principal building. Along the side property lines behind the front facade and along the rear property line a wall or fence may be six feet in height. Arbors and trellises are permitted in the front yard and may be located along property lines. The maximum height for arbors and trellises shall be ten feet. Above walls and fences, architectural features of up to 12 inches in height shall be allowed, spaced a minimum of four feet apart.
- c. Chain link fences shall not be visible from public rights-of-way. Chain link fences shall be vinyl coated using only black or dark green colors.

5. *Outbuildings.*

- a. Outbuildings shall be located behind the rear facade of the principal building or in rear one half of the property subject to a minimum five-foot side and rear yard setbacks from the property line. On corner lots the side setback shall be ten feet. There shall not be less than five feet separation between an outbuilding and the principal building.

6. *Curb cuts.*

- a. Where buildings do not have alleys in the rear of the property, not more than one curb cut shall be permitted for every 50 feet of frontage. However one curb cut shall be permitted for a single family residence utilized as a residence regardless of the existence of a rear alley.
- b. For properties with access from a rear alley, no curb cuts shall be permitted.

7. *Trees.*

- a. When a permit for new construction or renovation is issued, the owner shall be responsible for planting two shade trees no closer than three feet and no further than five feet from the right-of-way that abuts the front property line. All required shade trees, as defined by chapter XII of this Code, shall be 14 feet in height at installation, and have a DBH of not less than two and one-half inches, and be selected from the CRA landscape palette, if adopted by the city. The development director may grant a reduction for existing trees that meet these requirements.

8. *Buffer for single family residential.*

- a. A buffer for the single family neighborhood on the west side of NW North River Drive shall be provided. The buffer shall conform to section [6.04.00, Landscaping](#), of this Code.